

eTag ID (5-Digit Picking Label) Setting Instructions

1. Address (ID) setting

When the tag is in the non-display state or the idle state (after the picking data comes, press the confirmation button, but does not receive the 07 display off command, the same below), press and hold the up button for 3 seconds, and the tag enters the address setting mode, the digital tube displays the current address number, to modify the address number, you can press the up key +1, press the key -1 to adjust, for quick adjustment, you can press the confirmation key and then press the up and down keys to add 10 and subtract 10 Operation, after adjusting to the address to be set, press and hold the key for 3 seconds, the label saves the currently set address and exits the address setting mode, and the display is turned off at the same time.

2. Quickly check the address and confirmation key lights

When the label is in the non-display state or idle state, press the up and down keys at the same time. When pressed, the digital tube displays the local address, and the light of the confirmation key is displayed. When the label is released, the display is turned off. The cycle display between colors can be used to inspect the lights of 7 colors at the factory, and it can also quickly check the lighting effects for the user to choose the most suitable light color on site, and it is also convenient to quickly check the address of the machine on site. In the idle state, the lights and digital tubes are displayed. If the background cannot send the 07 display off command in time, press and release the up and down keys at the same time, and the display can also be turned off.

3 data modification function

When the label is lit from 01 02 03 04 and the data is displayed, if the actual quantity of the goods operated cannot meet the quantity required by the display, you can press the up and down keys to add 1 minus 1 to modify the data displayed by the red digital tube to the actual quantity of goods operated. The data sent to the background when the confirmation key is pressed is the modified data.