

RollerBelt LB100

INS + QR Code + 50kg load









440 N. Wolfe Rd.
Sunnyvale, CA 94085
Email: sales@liftians.com
Tel: 408-771-6628
WEB: www.liftians.com

Product Features

1. The QR code autonomous navigation mode is adopted for rapid deployment. The equipment only needs to scan the environment to build a map and achieve an accurate positioning of ± 10 mm.
2. The load weight can be up to 50kg, suitable for light item transporting.
3. The equipment adopts the modular design of the whole machine, which makes assembly and maintenance more convenient.
4. The battery can last for more than 8 hours with a full load, and the robot can automatically charge with low power (can be set per customer's requirements).
5. Cluster scheduling in the robot control system allows viewing work status, charge level, location and other information of all robots at the same time, and all devices may be scheduled through this.
6. Robots are equipped with lidar safety barrier avoidance, front contact anti-collision bar, left and right emergency stop buttons, and multiple mechanisms to ensure equipment and cargo safety.
7. With automatic path planning & realized unmanned operation, your staff only need to give instructions through the control terminal.
8. Infrared detection to ensure proper object placement

Dimensions




Specifications

Basic Specifications	NAME	RollerBelt AMB
	MODEL	LB100
	Loading	50KG
	Self-weight	120KG (±5KG)
	Dimension (L * w * h) mm	L690*W450*H870mm
	Navigation mode	Inertia + QR Code
	Communication Mode	WIFI
	Debug interface	Open interface
Moving Performance	Driving mode	Servo motor / two-wheel differential drive
	Positioning accuracy (mm)	±10mm
	No load maximum speed	1.5m/s
	With load maximum speed	1m/s
	Charging mode	Off line charging / automatic charging
	Endurance time	≥8H
	Max slope	≤2°
Battery Performance	Battery type	Lithium battery 48V
	Battery capacity	10AH
	Charging time	1.5~2H
	Battery life	2000 cycles, capacity ≥ 80%
Security	Anti-collision mode	Front and rear Lidar obstacle avoidance
	Emergency stop	Front and rear emergency stop buttons

Applications

1. Automate loading and unloading of totes and bins from conveyors
2. Flexibility to extend existing workflows
3. Fully controlled via Liftians systems



Usage and Precautions

1. Only use Liftians chargers
2. Prohibit unauthorized personnel around the work area
3. In case of abnormal noise / vibration / errant response, immediately stop using and notify Liftians for repair
4. The charging system shall be placed in a dry / ventilated / dust-free environment